# SKF 40PGAS

Compact pneumatically operated lubrication pumping unit for SKF MonoFlex single-line lubrication systems





Modular and mechanical adjustable B-dosers are used in SKF MonoFlex applications.



# SKF MonoFlex lubrication systems

- automatic lubrication system for demanding conditions
- modular and modifiable system
- lubrication data on display all the time
- data stored in control system memory
- dosers selected by points
- entire operation is adjustable
- additional equipment with quick coupling
- safe, supervised and environmentally friendly





### Pump 40PGAS

• splash-proof pneumatic pump and stainless steel tank; spring-loaded intermediate piston in tank with electric low level alarm with led-light for lubricant level and integrated pressure switch

#### Control center ST102 or ST102P


- electric, completely automatic control unit
- adjustable intervals for lubrication, 5 to 120 min, and pressurization, 1 to 10 min
- automatic pressure switch monitoring for lubrication pressure increase and decrease

#### **B-dosers**

• positive operating piston dosers in steel with dose size 20 to 500 mm<sup>3</sup>/lubrication point

## Piping


- for header 8x1 yellow chrome tube or 8/4 canvas reinforced nylon hose
- for lubrication 4x1 yellow chrome tube or 8/4 canvas reinforced nylon hose



© SKF Group 2014

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB LS/P2 11678 EN · February 2014





#### Tecnical specifications SKF 40PGAS-24V

Output	40 cm <sup>3</sup> /stroke
Reservoir	2 l, 4 l and 10
Pressure ratio	1:16
max. pneumatic connection	10 bar
Connection	R 1/4 in.
Voltage	24 V
Protection rating	IP65
Weight (reservoir filled)	13 kg
Height	360 mm
Width	350 mm
Length	170 mm

SKF lubrication systems e-mail: skf-lube@skf.com

